

06/16/99

1c598 U.S. PRO

IBM Docket No. FR9-98-041

In the United States Patent and Trademark Office Patent Application Transmittal

Transmitted herewith for filing is the Patent Application of:

Inventors(s): Claude Basso, Philippe Damon

For: Method for Extending the Crankback Procedure to Any Asynchronous Transfer Mode System

1c598 U.S. PRO
09/334414
06/16/99

Enclosed are

- 12 pages of specification, including 12 claims, plus 3 sheets of drawings.
- x An assignment of the invention to International Business Machines Corporation, Armonk, New York 10504.
 - x A certified copy of a/an **European** application.
 - x Declaration and Power of Attorney.
PTO-1449 & references
 - x A return post card
- Other:

Filing Fee Calculation (For Other Than Small Entity)

Basic Fee:							\$760.00
Claims Fees:		Filed	Limit	Extra		Rate per Extra	
Total claims:		12	20	0		\$18.00	\$0.00
Independent claims:		3	3	0		\$78.00	\$0.00
1	Multiple Dependent Claim Presented					\$260.00	\$260.00
Total							\$1,020.00

Please charge Deposit Account 09-0464 for the Total set forth above. The Commissioner is authorized to charge payment of any additional filing fees required under 37 CFR §1.116 and any patent application processing fees under 37 CFR §1.117 or to credit any overpayment to the identified account. A duplicate copy of this sheet is enclosed.

Express Mail Certificate

Express Mail Label No: EJ113458146US

Date: June 16, 1999

I hereby certify that I am depositing the papers identified above with the U.S. Postal Service "Express Mail Post Office to Address" service on the above date, addressed to the Commissioner of Patents and Trademarks, Washington, DC 20231

Linda Dupont

BY: Gerald R. Woods

Gerald R. Woods

Attorney of Record Reg. No. 24,144

Date: June 16, 1999

IBM Corporation 972/B656

Intellectual Property Law

PO Box 12195

Res. Tri. Park, NC 27709

Telephone: 919-543- 7204 FAX 919-543-3634

FR998041

APPLICATION FOR UNITED STATES PATENT

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, **Claude Basso and Philippe Damon** citizens of **France**, invented
new and useful improvements in

**Method for Extending the Crankback Procedure to Any Asynchronous Transfer Mode
System**

of which the following is a SPECIFICATION:

Method for Extending the Crankback Procedure to any Asynchronous Transfer Mode System

Technical field

The present invention relates to the establishment of Asynchronous Transfer Mode (ATM) connections by using ATM forum signaling standards and particularly to a method for extending the crankback procedure to any ATM system.

Background

Different techniques have been developed for transporting information over a network, such as packet switching techniques whereby digitized data is arranged into so-called bit packets, and circuit switching techniques. In packet switching, bit packets may either be of fixed length like in the Asynchronous Transfer Mode (ATM) where the packets, also called cells, are all of a conventional fixed length, or be of variable length.

ATM has been recognized as the common base on which different types of services and networks can operate. The ATM technology can efficiently combine the transmission of speech, video, audio sound (what is commonly called multimedia traffic) and computer data into the wired network. Furthermore, ATM has proven to scale well from very high speed network infrastructure (the information highways) to customer premises networks. One of the great advantages of the ATM technology is the fact that it can guarantee some level of service when an ATM connection is set up. Such guarantees can correspond to transmission rate, transmission latency and information loss. They can be achieved mainly because the ATM architecture assumes that the transmission media are almost error free.

Before data are exchanged between a source Data Terminal Equipment (DTE) and a destination DTE, in an ATM network, a routing procedure takes place during which the Control Point of the entry border node determines the best route from the source DTE to the destination DTE. Afterwards, the origin Control Point (in the entry border node) sends a connection set-up message, a copy of is being delivered to the control point of every switching node on the route.

When the route has been established, a confirmation message is sent back to the entry border node which can then initiate the exchange of information between the source DTE and the destination DTE.

An ATM network generally uses the Private Network Network Interface (PNNI) protocol. In such a protocol, a Designated Transit List (DTL) containing the list of nodes and port identifiers defining the path from the source DTE to the destination DTE is added to the set-up message and is used as a route vector along the path.

When interconnecting an ATM network running the PNNI protocol with another network through an Interim InterSwitch Protocol (IISP) interface, no dynamic routing information is exchanged between the networks and it is impossible to use procedure such as Crankback (used in PNNI protocol) to ensure that a connection will be set-up even if a part of the other network is down.

When a set-up message is rejected through an IISP interface, there is no crankback information element in the clearing message (it is only defined on a PNNI interface). Therefore, only a regular call clearing message is received by the entry border node from the IISP interface. Such a clearing message only contains a cause information element. Furthermore, no retry is performed.

Several approaches have been used to remedy this type of problem. One solution consists in just doing nothing at all except waiting for the failing part of the network to recover. Of course, this solution is unacceptable because it may take a very long time. During that time many users cannot use the network.

Another approach is to get rid of IISP interface everywhere and to use PNNI protocol with the hierarchy everywhere. This is technically valid but it is almost impossible in the real-life environment for many reasons. First, not all products implement the PNNI protocol, while all of them implement the IISP. Second, a product may be able to implement the cases, but the PNNI

protocol is a feature the customer has to pay for. The customer may not want to pay for it, may not want to change his network at all, and therefore may want to keep the IISP interfaces.

Still another approach consists in defining a new type of interface which would be an IISP-like with some extended feature which would solve the problem. This is not very good because it would be like some new proprietary protocol. In that case, this interface would not be compatible with current ATM Forum standards, and especially not compatible with the IISP interface. The consequence is that interoperability is completely jeopardized.

Accordingly, there is a need for a mechanism which extends the current standards procedures defined by the ATM Forum so that it becomes possible to solve the above problem cases without violating any standard procedure.

Summary of the invention

The main object of the invention is therefore to provide a method for extending the crankback procedure to any asynchronous transfer mode system without violating the existing standard procedure.

Another object of the invention is to provide a data transmission system including at least two links not supporting the PNNI protocol with an extension of the crankback procedure.

The invention relates to a method for extending the crankback procedure in an Asynchronous Transfer Mode (ATM) system composed of at least a first data network comprising a plurality of switching nodes interconnected by connection lines and including end switching nodes each being connected to at least a Data Transmission equipment (DTE) and being used either as an entry border node when it is connected to a source DTE or an exit border node when it is connected to a destination DTE, the network using a routing protocol of the type wherein a best route between a source DTE and a destination DTE is determined in a control point associated

with the entry border node to which is connected the source DTE and wherein a set-up message is sent by the entry border node, and a second data network including at least one DTE to be used as destination DTE in an exchange of data with a source DTE connected to the first data network and being interconnected with the first data network by means of at least two links not supporting the routing protocol. This method consists, when the exit border node of the first data network receives a clearing message on one link indicating that the set-up message has been rejected because the best route is blocked anywhere in the second data network, in building a crankback information element to be added to the clearing message for enabling the entry border node to find an alternate route avoiding the portion of the preceding best route which is blocked.

Brief description of the drawings

The objects, characteristics and advantages of the invention will become clear from the following description given in reference to the accompanying drawings wherein:

Fig. 1 is a block-diagram representing a connection between a source DTE and a destination DTE through a first ATM network and a second ATM network connected there between by two IISP links.

Fig. 2 is a block-diagram representing a connection between a source DTE and two destination DTEs having the same address through an ATM network to which are connected the two destination DTEs by means of UNI links.

Fig. 3 is a flow chart of the crankback extension procedure according to the invention.

Detailed description of the invention

In reference to Figure 1, it is assumed that a first ATM network 10 is interconnected with another ATM network 12 by means of two IISP links 14 and 16. Assuming that DTE 18 wants to exchange information with DTE 20, entry border node 22 to which is connected DTE 18 selects the best route by using the routing protocol supported by PNNI, this best route in network 10 being {node 22, node 24}. Then, node 24 has no other choice than IISP link 14 to reach the second ATM network 12 and the best path in this network to reach DTE 20, that is {node 26, node 28}.

Assuming that the link between node 26 and exit border node 28 is blocked as illustrated in Figure 1 by a cross, a clearing message is sent back by node 26 to node 24 (dashed line). If this clearing message contains a cause for which crankback may be generated, a crankback information element is created by node 24 and added to the clearing message to be forwarded to entry border node 22. Entry border node 22 tries to find an alternate route to reach exit border node 28. In the present case, an alternate route is {node 22, node 30} in network 10, link IISP 16 and {node 32, node 28} in network 12. Then, a call set-up message is forwarded by node 22 along this alternate route.

Note that, in the case illustrated by Figure 1, the route is blocked between the two nodes 26 and 28. The route could have been blocked because IISP link 14 is no longer valid. In such a case, a clearing message is generated by node 24 and contains originally the crankback information element.

Figure 2 illustrates the case where the first ATM network is linked to two DTE devices 34, 36 by two UNI links 38 and 40. Note that it does not matter that the two UNI (User-Network-Interface) links are connected directly to first network 10 or indirectly by means of a second network 42 represented by a dashed line in the figure.

Assuming that DTE 18 wants to exchange information with DTE 34, the best route determined by entry border node 22 is {node 22, node 24} in network 10 and then UNI link 38 to DTE 34. If, for any reason, DTE 34 is out of order, node 24 generates a crankback information element as in the preceding example and adds it in the clearing message sent back to entry border node 22. This one finds an alternate path which is {node 22, node 30} in network 10, and UNI link 40 to reach DTE 36 that has the same address as DTE 34 which has failed.

The flow-chart of the method steps carried out by the node which generates the crankback information is represented in Figure 3. After receiving the clearing message (50), the node such as node 24 in Figure 1 and 2, checks whether the link just after it on the route is a PNNI link (52). If so, the clearing message is forwarded downward to the entry border node (54). If not the cause information element is extracted from the clearing message (56). Definition of causes is provided in UNI 3.0 - Annexe E of the ATM Forum, wherein several groups of causes are defined, such as the Normal group. Then, it is determined whether the cause is really a cause requiring a rerouting (58). Indeed, some causes do not require to generate a crankback information, such as for example, cause 31 of the Normal group which corresponds to "normal call clearing" from the end system. In such a case, the clearing message is transmitted to the entry border route (54). The definition of the cause filter which is applied in step 58, depends upon the implementation of the invention. Indeed, the cause element as defined in the ATM Forum comprises three different fields: "location", "value", and "diagnostic", and the cause filter may apply to any of these fields. In a preferred embodiment of the invention, the cause filter applies only to the "value" field. Furthermore, the cause filter may be programmed statically by the network administrator or user, or dynamically by the network itself according to statistic data.

If the cause justifies a crankback generation (for example when the resources are unavailable), the node creates a crankback information element (60) which contains information as mentioned hereafter. This crankback information element is then added to the clearing message (62) which is transmitted to the entry border node.

The crankback information element contains, in the procedure implemented by the PNNI protocol:

the blocked transit type which can be “succeeding”, “node” or “preceding”

the block transit identifier which depends on the blocked transit type and is empty if the types is “succeeding”

5 identifies the blocked node if the type is “node” identifies the node that is preceding the blocked link if the type is “preceding”

the crankback cause which is generally the information received in the clearing message.

Therefore, in a system in which the method according to the invention is implemented, a way to specify that a link not supported by the PNNI protocol (such as IISP or UNI link) is blocked is to create an information element with the blocked transit type being “preceding” and wherein only the identifier of the preceding node is not zero

Claims

1. In an Asynchronous Transfer Mode (ATM) system composed of at least a first data network (10) comprising a plurality of switching nodes interconnected by connection lines and including end switching nodes each being connected to at least a Data Transmission equipment (DTE) and being used either as an entry border node (22) when it is connected to a source DTE (18) or an exit border node (28) when it is connected to a destination DTE (20), said network using a routing protocol of the type wherein a best route between a source DTE and a destination DTE is determined in a control point associated with said entry border node to which is connected said source DTE and wherein a set-up message is sent by said entry border node, and a second data network (12) including at least one DTE to be used as destination DTE in an exchange of data with a source DTE connected to said first data network and being interconnected with said first data network by means of at least two links (14, 16) not supporting said routing protocol; method for extending the crankback procedure over all said system consisting, when the exit border node of said first data network receives a clearing message on one of said links indicating that said set-up message has been rejected because said best route is blocked anywhere in said second data network, in building a crankback information element to be added to said clearing message for enabling said entry border node to find an alternate route avoiding the portion of said best route which is blocked.

2. The method according to claim 1, wherein said crankback information element includes a blocked transit type which can be "preceding", "node" or "succeeding", a blocked transit identifier depending on said blocked transit type and a crankback cause.

3. The method according to claim 2, wherein said blocked transit type is "preceding" and said blocked transit identifier identifies the node preceding the link not supporting said routing protocol as being blocked.

1 4. The method according to claim 1, 2 or 3, wherein said links not supporting said routing
2 protocol are Interim Inter switch Protocol (IISP) links.

1 5. The method according to claim 1, 2 or 3, wherein said links not supporting said routing
2 protocol are UNI links.

1 6. Asynchronous Transfer Mode (ATM) system composed of at least a first data network
2 (10) comprising a plurality of switching nodes interconnected by connection lines and including
3 end switching nodes each being connected to at least a Data Transmission equipment (DTE) and
4 being used either as an entry border node (22) when it is connected to a source DTE (18) or an
5 exit border node (28) when it is connected to a destination DTE (20), said network using a
6 routing protocol of the type wherein a best route between a source DTE and a destination DTE is
7 determined in a control point associated with said entry border node to which is connected said
8 source DTE and wherein a set-up message is sent by said entry border node, and a second data
9 network (12) including at least one DTE to be used as destination DTE in an exchange of data
10 with a source DTE connected to said first data network and being interconnected with said first
11 data network by means of at least two links (14, 16) not supporting said routing protocol;
12 said system further comprising means for extending the crankback procedure over all said system
13 in building, when the exit border node of said first data network receives a clearing message on
14 one of said links indicating that said set-up message has been rejected because said best route is
15 blocked anywhere in said second data network, a crankback information element to be added to
16 said clearing message for enabling said entry border node to find an alternate route avoiding the
17 portion of said best route which is blocked.

1 7. The system according to claim 6, wherein said crankback information element includes a
2 blocked transit type which can be "preceding", "node" or "succeeding", a blocked transit
3 identifier depending on said blocked transit type and a crankback cause.

1 8. The system according to claim 7, wherein said blocked transit type is “preceding” and said
2 blocked transit identifier identifies the node preceding the link not supporting said routing
3 protocol as being blocked.

1 9. The system according to claim 6, 7 or 8, wherein said links not supporting said routing
2 protocol are Interim Inter switch Protocol (IISP) links.

1 10. The system according to claim 6, 7 or 8, wherein said links not supporting said routing
2 protocol are UNI links.

1 11. For use in a system having a first network and a second network, said first network
2 having at least one entry border node connected to a source node, said first network adhering to a
3 routing protocol which includes the use of a crankback procedure to inform the entry border node
4 of a path failure within the first network, said second network having at least one exit border
5 node connected to a destination node, said second network including at least some elements
6 which do not use a crankback procedure, said first and second networks being interconnected
7 through a plurality of links connecting a plurality of border nodes within each network, a method
8 of extending the crankback procedure to cover path failures in said second network, said method
9 being implemented in a border node in said first network on a proposed path between the source
10 node and the destination node and comprising the steps of:

11 monitoring messages returned from the second network relating to the proposed path for
12 a clearing message indicative of a failure in the proposed path anywhere in the second
13 network;

14 in response to detection of said clearing message, generating a crankback information
15 element;

16 modifying said clearing message by adding said generated crankback information
17 element; and

18 forwarding said modified clearing message to the entry border node.

1 12. The method according to claim 11 wherein said crankback information element includes
2 a blocked transit type field, a blocked transit identifier field and a crankback cause field.

Method for Extending the Crankback Procedure to any Asynchronous Transfer Mode System

Abstract

Method for extending the crankback procedure in an Asynchronous Transfer Mode (ATM) system composed of at least a first data network (10) comprising a plurality of switching nodes interconnected by connection lines and including end switching nodes each being connected to at least a Data Transmission equipment (DTE) and being used either as an entry border node (22) when it is connected to a source DTE (18) or an exit border node (28) when it is connected to a destination DTE (20), the network using a routing protocol of the type wherein a best route between a source DTE and a destination DTE is determined in a control point associated with the entry border node to which is connected the source DTE and wherein a set-up message is sent by the entry border node, and a second data network (12) including at least one DTE to be used as destination DTE in an exchange of data with a source DTE connected to the first data network and being interconnected with the first data network by means of at least two links (14, 16) not supporting the routing protocol. Such a method consists, when the exit border node of the first data network receives a clearing message on one link indicating that the set-up message has been rejected because the best route is blocked anywhere in the second data network, in building a crankback information element to be added to the clearing message for enabling the entry border node to find an alternate route avoiding the portion of the route which is blocked.




FIG. 1




FIG. 2




FIG. 3

IBM Docket No. FR9-98-041

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**Method for Extending the Crankback Procedure to any Asynchronous Transfer
Mode**

the specification of which is identified by the attorney (IBM) Docket Number appearing above.

I hereby state that I have reviewed and understand the contents of the above- identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

<u>Number</u>	<u>Country</u>	<u>Day/Month/Year</u>	<u>Priority Claimed</u>
98480058.1	Europe	28/08/98	Yes

I hereby claim the benefit (a) under Title 35, United States Code, §119(e) of any U.S. application listed below and identified as a provisional application or (b) under Title 35, United States Code, §120 of any U.S. application listed below and not identified as a provisional application, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior U.S. application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Prior U.S. Applications

<u>Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
-------------------	--------------------	---------------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

IBM Docket No. FR9-98-041

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Daniel E. McConnell, Reg. No. 20,360; Kenneth A. Seaman, Reg. No. 28,113; Joscelyn G. Cockburn, Reg. No. 27,069; Gerald R. Woods, Reg. No. 24,144; John D. Flynn, Reg. No. 35,137; Horace St. Julian, Reg. No. 30,329; Joseph C. Redmond, Jr., Reg. No. 18,753; John E. Hoel, Reg. No. 26,279; Christopher A. Hughes, Reg. No. 26,914; and Edward A. Pennington, Reg. No. 32,588.

Send all correspondence to: Gerald R. Woods, IBM Corporation 972/B656; PO Box 12195; Research Triangle Park, NC 27709.

First Inventor:

Claude Basso

Signature:

Basso

June 16th 1999

Date

Residence:

252 Chemin de la Lanterne
06000 Nice
France

Citizenship:

French

Post Office Address:

Same

Second Inventor:

Philippe Damon

Signature:

SDAMON

June 16th 1999

Date

Residence:

9 Chemin des Plateaux Fleuris
06800 Cagnes-sur-mer
France

Citizenship:

French

Post Office Address:

Same

0934414 051699